
EpoxyGel Booster

Technical Specifications



Accelerating additive for epoxy gels.

Product description	EpoxyGel Booster is an accelerator additive for epoxy gels Adding EpoxyGel Booster as a third component accelerates the reaction of the epoxy system, reducing the time required for the adhesive or grout to be ready for use.
----------------------------	--

Certification	Zherorisk® EpoxyGel technology
----------------------	--------------------------------

Uses	Interiors Floors – walls Radiant heating systems SPA – Hammam Indoor wet areas – bathrooms and showers Industrial flooring Dairies, abattoirs, food processing industries Residential, public, commercial building
-------------	---

Technical Specifications	Appearance	Straw-coloured liquid
	Customs heading	32099000
	Shelf life	24 months in the original packaging in a dry

place.

Application Specifications

Mixing ratio	2%
Mixing ratio	Pre-measured 50 g packs for the 2.5 kg pack of Starlike® Pro.
Mixing ratio	2 pre-measured 50 g packs for the 5 kg pack of Starlike® Pro, Starlike® Easy or PowerGel® Pro Max
Mixing ratio	Pre-measured 200 g packs for the 10 kg pack of PowerGel® Pro or PowerGel® Pro Max
Specific gravity of the mixture	1.60 kg/dm ³
Pot life	Approx. 60 minutes
Permissible application temperatures	From +5°C to +30°C
Ready for foot traffic	About 6 hours
Operating temperature	From -40°C to +90°C
Cleaning of equipment	With water when the product is fresh. Mechanically once the product has hardened.

Preparation of the mix

Add the pre-measured sachet of EpoxiGel Booster, depending on the size, after mixing the catalyst (part B), and mix thoroughly at low speed until a homogeneous mixture is obtained.

Application

See the 'Application' section for the selected product

Warnings

Observe the mixing ratio.
Do not mix the product with solvents.
Do not add lime, cement or other foreign materials to the product.
Do not mix partial quantities of the components without using scales; incorrect mixing ratios would result in the product not curing properly.
Do not add to Starlike® Crystal.
Do not use outdoors.
Do not use the product for applications not listed on this technical data sheet.
If in doubt, please consult the Litokol S.p.A. Technical Support Department.

Safety Information

For the safe use of our products, please refer to the latest version of the Safety Data Sheet, available at www.litokol.com
PRODUCT FOR PROFESSIONAL USE

Legal notices

The information and specifications set out in this technical data sheet are based on our best experience.

However, as we are unable to directly influence site conditions or the execution of the works, these are general guidelines which do not in any way bind our Company.

We therefore recommend carrying out a preliminary test to verify the product's suitability for the intended use; in any case, anyone intending to use it is required to determine whether or not it is suitable for the intended use and, in any event, assumes all liability that may arise from its use.

Always refer to the latest updated version of the Technical Data Sheet, available on the website www.litokol.com

Product details **No. 381**

Revision **No. 0**

Date: **05 25**

Litokol

Litokol Lab Spa Via G. Falcone 13/1 42048 Rubiera RE Italy
Tel. +39 0522 622811 info@litokol.com www.litokol.com