
Starlike® Remover

Technical Specifications



High-performance cleaning gel for the complete removal of hardened residues of epoxy gels, resins and paints

Product description

Starlike® Remover is a solvent-based stripping gel for the rapid and thorough removal of cured and polymerised epoxy residues, even some time after grouting. Suitable for removing and dissolving hardened epoxy grout from joints.

Thanks to its gel-like viscosity, Starlike® Remover is suitable for cleaning floors and walls, both indoors and outdoors.

Performance

Versatile, it can be used on tiles, porcelain stoneware and glass.

Also effective on epoxy and polyurethane resins and industrial enamels.

Its hyper-active formula is designed to penetrate and dissolve even the thickest, oldest and most polymerised deposits.

Thanks to its thick, viscous gel formula, it is easy to apply, even on vertical surfaces.

Uses

When used undiluted, the cleaner, thanks to its powerful breaking-down action, is particularly effective at removing set residues of epoxy gels such as Starlike® Pro, Starlike® Crystal or Starlike® Easy.

Effective for removing old epoxy grouts.

Product specifications

Appearance	Thick transparent gel
Colour	Light blue
Odour	Characteristic
Customs heading	38140090
Packaging	0.75 l metal bottles
Shelf life	24 months in the original packaging, away from heat sources and direct light. Keep away from frost.

Application Specifications

Working time	10–20 minutes up to a few hours
Flammability	Yes
Specific gravity	0.93 kg/l
Application	Paintbrush or smooth steel spatula
Permissible application temperatures	From +5°C to +35°C
Coverage	3–10 m ² /l

Application

Shake well before use.
The product is ready to use and requires no dilution.
Apply an even layer of the product to the areas to be removed using a brush or steel trowel.
Leave Starlike® Remover to work until the residues to be removed have softened.
Normally, around 10–20 minutes is sufficient for removing streaks, and 1 to 8 hours for removing hardened grout.
Then remove any residual epoxy mortar using a metal trowel.
Wipe with a clean, dry cloth to remove the gel and rinse thoroughly with clean water.
If necessary, carry out a second wash.

Warnings

Apply the product at temperatures between +5°C and +35°C
Do not dilute the product with water or solvents
Before use, protect doors, window frames, rubber seals, furniture, taps, metal or PVC profiles and all surfaces that could be damaged by direct contact with the cleaning agents
Change the rinse water frequently
In the event of accidental spills, absorb the product using an absorbent material (paper, sawdust, vermiculite, etc.) and dispose of it in a suitable container
Do not smoke whilst using the product.
Do not use on products that are not solvent-resistant, such as: plastics, PVC, linoleum, decorative enamels, etc.
For honed, lapped or polished natural stone tiles, carry out a preliminary test to ensure that the product does not dull the surface
Do not use the product for applications not listed on this technical data sheet
For further information, please contact Litokol's Technical Customer Service on +39-0522-622811 or via customercare@litokol.com

Safety Information

For the safe use of our products, please refer to the latest version of the Safety Data Sheet, available at www.litokol.com
PRODUCT FOR PROFESSIONAL USE

Legal notices

The information and specifications contained in this technical data sheet are based on our best experience.

However, as we are unable to directly influence site conditions or the execution of the works, these are general guidelines which do not in any way bind our Company.

We therefore recommend carrying out a preliminary test to verify the product's suitability for the intended use; in any case, anyone intending to use it is required to determine whether or not it is suitable for the intended use and, in any event, assumes all liability that may arise from its use.

Always refer to the latest updated version of the Technical Data Sheet, available on the website www.litokol.com

Product details **No. 423**

Revision **No. 0**

Date: **05 25**

Litokol

Litokol Lab Spa Via G. Falcone 13/1 42048 Rubiera RE Italy
Tel. +39 0522 622811 info@litokol.com www.litokol.com