
X-Cleaner Forte

Technical Specifications



Pro Acid Descaling Cleaner for deep cleaning of ceramic tiles. Effective at removing cementitious grout residues. Removes cement residues, lime, efflorescence, rust and limescale.

Product description

X-Cleaner Forte is a concentrated, acid-pH liquid cleaner for post-construction cleaning.

The product, formulated with inhibited acids and specific detergents, replaces traditional acids, delivering even better results in the deep cleaning of recently laid ceramic surfaces.

Performance

Suitable for removing salt efflorescence

Water-based product.

Mild on cement-based grout. Does not alter the colour of the grout lines

Not subject to transport hazard classification.

Excellent cleaning power

Uses

Suitable for the rapid removal of cement residues and cementitious sealants, salt and limescale deposits, tempera paint and lime from ceramic tiles, porcelain stoneware, glass mosaics, terracotta, aged marble, etc., on both internal and external floors and walls.

When used correctly, the product does not damage grouting carried out with traditional cementitious grouts and is capable of removing any efflorescence that may form on the surface, restoring a uniform colour to the grout.

Product specifications

Appearance	Transparent liquid
Colour	Light blue
Odour	Slightly scented
Customs heading	3402909000
Responsible packaging	1-litre recycled plastic bottle. 5-litre recycled plastic jerrycan.
Shelf life	36 months in original packaging, away from heat sources and direct light. Keep away from frost.

Application Specifications

Working time	5–10 minutes
Flammability	No
pH	2,1 - 2,9
Specific gravity	1.04 kg/l
Application	Starlike® white sponge or felt
Permissible application temperatures	From +5°C to +35°C
Coverage	10–20 m ² /l

Application

Shake well before use.
The product should almost always be used diluted.
Dilute the product from 1:1 to 1:10 with cold water, depending on the material and the type of dirt to be removed.
Pour the liquid onto the surface to be cleaned and spread it evenly.
Leave to act for approximately 5–10 minutes and then use a white felt pad to remove any remaining residue or crusts.
Remove any residual liquid from the surface using rags, a rubber scraper or a wet vacuum.
Finally, rinse thoroughly with clean water and dry with a clean cloth or towel.

Warnings

Do not use the product in too concentrated a form to avoid the risk of deposits
For grouted floors, it is advisable to wait at least 7 days after sealing before washing
Before use, protect doors, window frames, rubber seals, furniture, taps, metal or PVC profiles and all surfaces that could be damaged by direct contact with the detergent.
Change the rinse water frequently
In the event of accidental spills, absorb the product using an absorbent material (paper, sawdust, vermiculite, etc.) and dispose of it in a suitable container
For surfaces made of brushed marble, dilute the product with water in a ratio of 1:10; for tumbled marble, dilute the product with water in a ratio of 1:3
Do not use the product on marble or other polished calcareous materials, as these may lose their lustre
When handling the product, wear suitable protective clothing. Follow the instructions on the label and in the relevant safety data sheet
Do not use the product for applications not listed on this technical data sheet
For further information, please contact Litokol's Technical Customer Service on +39-0522-622811 or via customercare@litokol.com

Safety Information

For the safe use of our products, please refer to the latest version of the Safety Data Sheet, available at www.litokol.com
PRODUCT FOR PROFESSIONAL USE

Legal notices

The information and specifications contained in this technical data sheet are based on our best experience.

However, as we are unable to directly influence site conditions or the execution of the works, these are general guidelines which do not in any way bind our Company.

We therefore recommend carrying out a preliminary test to verify the product's suitability for the intended use; in any case, anyone intending to use it is required to determine whether or not it is suitable for the intended use and, in any event, assumes all liability that may arise from its use.

Always refer to the latest updated version of the Technical Data Sheet, available on the website www.litokol.com

Product details **No. 412**

Revision **No. 1**

Date: **09 26**

Litokol

Litokol Lab Spa Via G. Falcone 13/1 42048 Rubiera RE Italy
Tel. +39 0522 622811 info@litokol.com www.litokol.com