
X-Cleaner Scrub

Technical Specifications



Pro concentrated cleaner and degreaser, for removing dirt, waxes, resins and polymers prior to application on existing flooring. Also effective for deep cleaning of stubborn dirt

Product description

X-Cleaner Scrub is an alkaline liquid cleaner suitable for deep cleaning, both indoors and outdoors, of tiles, mosaics, porcelain stoneware, marble and natural stone affected by general and stubborn dirt resulting from normal use of the surfaces.

Ideal for cleaning floors and walls prior to installation over existing flooring.

Cleans synthetic flooring such as PVC, epoxy and polyurethane thoroughly.

Performance

Versatile, it can be used on all surfaces.

Water-based product.

Non-aggressive solution, also suitable for use on marble and natural stone

Avoid using hazardous or hard-to-source materials such as caustic soda

Allows direct application with cementitious adhesives when laying as an overlay

Excellent degreasing and wax-removing power

Product subject to no restrictions on transport by road, sea, air or rail

Uses

The product can be used undiluted or diluted in clean water, depending on the level of dirt to be removed

To dissolve particularly stubborn resins, waxes and polymers, the product should be used undiluted

When used as a degreasing cleaner to remove heavy and stubborn residues, even on acid-sensitive materials, the product must be diluted 1:2 with water.

For regular cleaning of the floor, the product should be diluted 1:6 with water

Removes rubber and tyre residues

Product specifications

Appearance	Liquid
Colour	Amber
Odour	Characteristic
Customs heading	3402909000
Responsible packaging	1-litre recycled plastic bottles
Shelf life	36 months in original packaging, away from heat sources and direct light. Keep away from frost.

Application Specifications

Working time	10–15 minutes
Flammability	No
pH	10,5 - 11,5
Specific gravity	1.04 kg/l
Application	White sponge or felt
Permissible application temperatures	From +5°C to +35°C
Coverage	8–10 m ² /l

Application

Shake well before use.

Apply the product at the recommended dilution and spread it directly onto the affected surface, distributing it evenly using a single-disc machine or a floor brush. Leave to act for approximately 10–15 minutes, scrubbing mechanically at regular intervals.

Once the desired time has elapsed, remove any residue. Pour a sufficient quantity of water onto the treated surface to re-emulsify the solution on the floor and remove any excess using a wet vacuum, rags or absorbent paper.

Warnings

Before applying the product, it is advisable to carry out a preliminary test on a small section of the material to assess its suitability for the intended use

Wear suitable protective clothing when handling the product. Follow the instructions on the label and the relevant safety data sheet

Before use, protect doors, window frames, rubber seals, furniture, taps, metal or PVC profiles and all surfaces that could be damaged by direct contact with the cleaning agents

Change the rinse water frequently

In the event of accidental spills, absorb the product using an absorbent material (paper, sawdust, vermiculite, etc.) and dispose of it in a suitable container

Do not use the product for applications not listed on this technical data sheet
For further information, please contact Litokol's Technical Customer Service
on +39-0522-622811 or via customer care@litokol.com

Safety Information

For the safe use of our products, please refer to the latest version of the
Safety Data Sheet, available at www.litokol.com
PRODUCT FOR PROFESSIONAL USE

Legal notices

The information and specifications contained in this technical data sheet are
based on our best experience.

However, as we are unable to directly influence site conditions or the
execution of the works, these are general guidelines which do not in any way
bind our Company.

We therefore recommend carrying out a preliminary test to verify the
product's suitability for the intended use; in any case, anyone intending to
use it is required to determine whether or not it is suitable for the intended
use and, in any event, assumes all liability that may arise from its use.

Always refer to the latest updated version of the Technical Data Sheet,
available on the website www.litokol.com

Product details **No. 415**

Revision **No. 0**

Date: **05 25**

Litokol

Litokol Lab Spa Via G. Falcone 13/1 42048 Rubiera RE Italy
Tel. +39 0522 622811 info@litokol.com www.litokol.com